

MAXFLO[®]-S800G

Shaker Bag Dust Collector for Pedestal Grinders



- Economical compact design dust collector
- Manual foot shaker cleaning system with dust pan
- 1HP motor with direct drive blower
- 800CFM, 120/1/60, (2) 4" collars
- Plug & Play, low maintenance, low operating cost
- Built-in silencer, 66 dbA
- Efficiencies up to 99.9% @ 0.3 micron

Powerful & affordable source capture collector.



ONE YEAR
LIMITED WARRANTY



DIVERSIFIEDAIR
SYSTEMS

MAXFLO IS A TRADEMARK OF
DIVERSIFIED AIR SYSTEMS

OUTSTANDING MAXFLO STANDARD FEATURES

MAXFLO S800G is designed to provide efficient, cost effective control of dry dusts from sanding, grinding, and other processes. Typically used for light to moderate concentrations of dry contaminates. The S800G collector is provided with manual bag shaker cleaning to minimize maintenance and reduce replacement filter costs. The shaker unit is a smaller sized collector and a low cost alternative to the self-cleaning cartridge dust collector.

The MAXFLO-S800G can be configured in a couple of different ways, as a floor mounted unit or a portable unit with casters. The MAXFLO-S800G unit is a self-contained, ready to be powered, compact source capture dust collector. The overall size of the collector is designed to fit under a standard work bench.



FEATURES

- Direct drive forward curved blower with a 1HP TEFC motor delivering 800 CFM at 3 inches external static pressure.
- 120/220 volt single phase
- Low noise level at 66 dbA
- Manual foot shaker to manually clean the filter bags
- Pull out drawer with a holding capacity of 0.9 cubic feet
- Standard 4 inch inlet collars
- Bubble gasket seal on blower and filter access doors
- 22 envelope pocket, flame retardant cotton sateen filters
- Total filter area is 55 square feet with toolless filter replacement
- Built-in silencer
- 16 ga metal construction with a heavy duty textured powder coat finish

| Unit Type | CFM | MTR HP | Weight (lbs) | Sound Pressure (dba) | L x W x H (in.) |
|-----------|-----|--------|--------------|----------------------|-----------------|
| S-800G | 800 | 1 | 200 | 66 | 25 x 24 x 29 |

OPTIONS

- Fork Lift Rails, Adds 2" to OAH
- Spark Trap, Adds 16.2" to OAL
- HEPA, 99.99%
- Swivel 5" casters
- 208/230/460V motor

Diversified Air Systems, Inc

5900 Concord Avenue Crestwood KY 40014 // Toll free: 800.264.8958 // Phone: 502.267.0333 // Fax: 502.267.4241
 www.maxfloair.com // info@maxfloair.com

Note: Specifications listed above may be modified to suit application. Contact D.A.S. or representative for information.

Continuous product improvement is a policy of D.A.S. Inc. Product features and specifications may be modified without prior notice.



ONE YEAR
LIMITED WARRANTY

CALL TODAY: 800.264.8958

MAXFLO is a trademark of Diversified Air Systems